

Komatsu Wheel Loader WA480-8 WH



WA480-8 WH

Horsepower	288 HP @ 2,000 rpm
Operating Weight in Lbs.	56,262-56,416
Full Turn Tip Load in Lbs.	36,299-36,520

Meeting the demands of waste management

Protect your wheel loader with customizable waste guarding packages, including custom guarding, joystick steering for easier maneuverability, and steering wheel placement to improve visibility.

Protection Features & Benefits

Cooling screens

Increase effective open area for airflow while reducing the amount of debris reaching the coolers.

Front window and light guards

Provides additional protection to the window and operator from large debris. Guards on the front and rear lights help protect against damage.

Front and rear frame under guard

Protect the engine oil pan, oil drain, and fuel tank drain. Reduces debris buildup and shields powertrain and hydraulic components.

Axle seal guards

Encloses the exposed surfaces of the fuel tank to minimize damage and transfers impact forces into the rear frame and counterweight.

Bucket cylinder guard

Guard and protect the bucket cylinder rod from falling debris.

Boom cylinder hose guards and wraps

Provides additional protection to the hydraulic hoses and protects from wear, abrasion, and cuts.

Fuel tank guard

Encloses the exposed surfaces of the fuel tank to minimize damage and transfers impact forces into the rear frame and counterweight.

Beacon lamp and additional work lights

The cab is pre-wired for a roof-mounted beacon or strobe light. Switches for the beacon and rear lights are integrated into the dashboard.

